Manufacturer (trade mark):	**Clover Germany**	Type/Model OEM:	Q2612A
Lot/Part number:	**521190EP**	Toner color(s):	**Monochrome**
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	2000		
Test device:	SCNCJ333874 / CNC9512003 / CNFD722580	Take over value of existing test protocol :	(box) Yes, from ISO19752
Test climate:			
Temperature:	22	Relative humidity:	53
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojić	Test location 2):	**TRS EUROPE**
Test date:	12.3.2010		

1)If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	2526	Yes		N/A
2	2749	Yes		N/A
3	2527	Yes	We use for A1 the	N/A
4	3539	Yes	MAX, for A2 the	N/A
5	2642	Yes	MEDIAN and for A3 the	N/A
6	2985	Yes	MIN value of the list at	N/A
7	2903	Yes	left	N/A
8	2586	Yes		N/A
9	2752	Yes		N/A

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	2000	Yes/no	Yes	N/A
2	2000	Yes/no	Yes	N/A
3	2000	Yes/no	Yes	N/A
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5)

BLACK

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	3539	2749	2526	2938
Yield V: (V1+V2+V3)/3=V	2000	2000	2000	2000

Alternative:

Yield A: Result of test after ISO/IEC 19752 Ā	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 V	
Reference to the test protocol:	
Test date:	
Result: EZ=Ā/V	1,47

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1: N/A

Average value of the 2 areas F comparing print V1: N/A

Difference is not higher than Δ*+-5 for Monochrom	N/A	Yes/no/Not Aplicable	N/A
Color difference ΔE≤18 for Color		Yes/no/Not Aplicable	N/A
Average value of the 2 areas F test print A2:	N/A		
Average value of the 2 areas F comparing print V2:	N/A		
Difference is not higher than Δ*+-5 for Monochrom	N/A	Yes/no/Not Aplicable	N/A
Color difference ΔE≤18 for Color		Yes/no/Not Aplicable	N/A
Average value of the 2 areas F test print A3:	N/A		
Average value of the 2 areas F comparing print V3:	N/A		
Difference is not higher than Δ*+-5 for Monochrom	N/A	Yes/no/Not Aplicable	N/A
Color difference ΔE≤18 for Color		Yes/no/Not Aplicable	N/A

Checking the fade (5.6.3)

BLACK

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	N/A
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	N/A
Result determination	1	6	A	F
Difference ΔL≤8	N/A	N/A	N/A	N/A
Difference within allowed parameters	N/A	N/A	N/A	N/A

BLACK

Test print A2				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	N/A
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	N/A
Result determination	1	6	A	F
Difference ΔL≤8	N/A	N/A	N/A	N/A
Difference within allowed parameters	N/A	N/A	N/A	N/A

BLACK

Test print A3				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	N/A
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	N/A	N/A	N/A	N/A
Color values 1 6 A F	1	6	A	F
The biggest deviation	N/A	N/A	N/A	
				N/A
Result determination	1	6	A	F
Difference ΔL≤8	N/A	N/A	N/A	N/A
Difference within allowed parameters	N/A	N/A	N/A	N/A

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters?	Yes
If not: Describe deviation	

Checking the grey page/color uniformity (5.6.5)

Are the lightness differences in between the acceptable parameters?	Yes
If not: Describe deviation	

Checking the background (5.6.6)

Is the background smudge in between the acceptable parameters (pattern B1)?	Yes
If not: Describe deviation	

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2)?	Yes
If not: Describe deviation	

Checking toner miscibility (5.6.8)

Is the toner miscibility given?	N/A
If not: Describe deviation	

OVERALL RESULT: **Passed**